

Refine Search

Search Results -

Term	Documents
MIL-STD	337
MIL-STDS	9
HUMIDITY	170261
HUMIDITIES	4749
HUMIDITYS	0
TEMPERATURE	1798241
TEMP	82268
TEMPS	781
TEMPERATURES	792403
ETHERNET	66916
ETHERNETS	577
(MIL-STD AND HUMIDITY AND TEMPERATURE AND ETHERNET).PGPB,USPT.	1

[There are more results than shown above. Click here to view the entire set.](#)

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L29	[]	[]
<input type="button" value="Refine Search"/>		
<input type="button" value="Recall Text"/>	<input type="button" value="Clear"/>	<input type="button" value="Interrupt"/>

Search History

DATE: Tuesday, August 29, 2006 [Purge Queries](#) [Printable Copy](#) [Create Case](#)

Set Name **Query**
side by side

Hit Count **Set Name**
result set

DB=PGPB,USPT; PLUR=YES; OP=ADJ

<u>L29</u>	MIL-STD and humidity and temperature and ethernet	1	<u>L29</u>
<u>L28</u>	L26 and 10% near 95%	3	<u>L28</u>
<u>L27</u>	L26 and 10 near 95%	0	<u>L27</u>
<u>L26</u>	operating near temperature and humidity and ethernet	180	<u>L26</u>
<u>L25</u>	Military near ethernet and humidity	0	<u>L25</u>
<u>L24</u>	rugged and harsh and ethernet near switch	1	<u>L24</u>
<u>L23</u>	L22 and ethernet	0	<u>L23</u>
<u>L22</u>	Military near switch	10	<u>L22</u>
<u>L21</u>	l13 and humidity	2	<u>L21</u>
<u>L20</u>	l13 and humidity and 0 near 60	0	<u>L20</u>
<u>L19</u>	L16 and 60 near degrees	0	<u>L19</u>
<u>L18</u>	L13 and 10 near 95%	0	<u>L18</u>
<u>L17</u>	L16 and humidity	2	<u>L17</u>
<u>L16</u>	L13 and temperature	43	<u>L16</u>
<u>L15</u>	L13 and operating near temperature	1	<u>L15</u>
<u>L14</u>	L13 and humidity	2	<u>L14</u>
<u>L13</u>	industrial adj ethernet	80	<u>L13</u>
<u>L12</u>	L11 and 60 near degrees	0	<u>L12</u>
<u>L11</u>	L10 and operating near temperature	3	<u>L11</u>
<u>L10</u>	industrial near ethernet	125	<u>L10</u>
<u>L9</u>	L8 and military	1	<u>L9</u>
<u>L8</u>	L7 and humidity	8	<u>L8</u>
<u>L7</u>	ethernet near switch and operating near temperature	58	<u>L7</u>
<u>L6</u>	L5 and operating near temperature	0	<u>L6</u>
<u>L5</u>	L1 and ethernet	11	<u>L5</u>
<u>L4</u>	L1 and military	0	<u>L4</u>
<u>L3</u>	L1 and industrial	0	<u>L3</u>
<u>L2</u>	L1 and ethernet near switch	0	<u>L2</u>
<u>L1</u>	370/372.ccls.	47	<u>L1</u>

END OF SEARCH HISTORY

Refine Search

Search Results -

Term	Documents
"10%"	636060
"10%S"	5
"95%"	281425
"95%S"	3
(26 AND ("95%" NEAR "10%")).PGPB,USPT.	3
(L26 AND 10% NEAR 95%).PGPB,USPT.	3

Database:	US Pre-Grant Publication Full-Text Database US Patents Full-Text Database
	US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins
Search:	<input type="text" value="L28"/>
	<input type="button" value="Refine Search"/>
	<input type="button" value="Recall Text"/>
	<input type="button" value="Clear"/>
	<input type="button" value="Interrupt"/>

Search History

DATE: Tuesday, August 29, 2006 [Purge Queries](#) [Printable Copy](#) [Create Case](#)

Set Name Query
side by side

Hit Count Set Name
result set

DB=PGPB,USPT; PLUR=YES; OP=ADJ

<u>L28</u>	L26 and 10% near 95%	3	<u>L28</u>
<u>L27</u>	L26 and 10 near 95%	0	<u>L27</u>
<u>L26</u>	operating near temperature and humidity and ethernet	180	<u>L26</u>
<u>L25</u>	Military near ethernet and humidity	0	<u>L25</u>
<u>L24</u>	rugged and harsh and ethernet near switch	1	<u>L24</u>
<u>L23</u>	L22 and ethernet	0	<u>L23</u>
<u>L22</u>	Military near switch	10	<u>L22</u>
<u>L21</u>	l13 and humidity	2	<u>L21</u>
<u>L20</u>	l13 and humidity and 0 near 60	0	<u>L20</u>

<u>L19</u>	L16 and 60 near degrees	0	<u>L19</u>
<u>L18</u>	L13 and 10 near 95%	0	<u>L18</u>
<u>L17</u>	L16 and humidity	2	<u>L17</u>
<u>L16</u>	L13 and temperature	43	<u>L16</u>
<u>L15</u>	L13 and operating near temperature	1	<u>L15</u>
<u>L14</u>	L13 and humidity	2	<u>L14</u>
<u>L13</u>	industrial adj ethernet	80	<u>L13</u>
<u>L12</u>	L11 and 60 near degrees	0	<u>L12</u>
<u>L11</u>	L10 and operating near temperature	3	<u>L11</u>
<u>L10</u>	industrial near ethernet	125	<u>L10</u>
<u>L9</u>	L8 and military	1	<u>L9</u>
<u>L8</u>	L7 and humidity	8	<u>L8</u>
<u>L7</u>	ethernet near switch and operating near temperature	58	<u>L7</u>
<u>L6</u>	L5 and operating near temperature	0	<u>L6</u>
<u>L5</u>	L1 and ethernet	11	<u>L5</u>
<u>L4</u>	L1 and military	0	<u>L4</u>
<u>L3</u>	L1 and industrial	0	<u>L3</u>
<u>L2</u>	L1 and ethernet near switch	0	<u>L2</u>
<u>L1</u>	370/372.ccls.	47	<u>L1</u>

END OF SEARCH HISTORY